

Nail In Anchor



Nail In Anchor • Metal

Hammer in fixing available in Steel and Zinc Alloy, suitable for use in concrete, masonry and some natural stone.

Part Number	Anchor Hole Size mm	Total Anchor Length mm	Max.Fixture Thickness mm	Flange Head Diameter mm	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
MDA06040	6	40	5	15	100	1.40	41.76
MDA06065	6	65	30	15	100	1.60	51.04



Nail In Anchor • Alloy

LANI06030	6	30	10	13	100	0.85	37.12
LANI06040	6	40	20	13	100	1.10	38.45
LANI06050	6	50	30	13	100	1.24	50.38



Nail In Anchor • Steel

MNI06030	6	30	10	13	100	0.85	37.12
MNI06040	6	40	20	13	100	1.10	39.11
MNI06050	6	50	30	13	100	1.24	52.37

Plastic Headed Nails

An A4/316 stainless steel nail, ring shanked with HDPE impact resistant poly head. UV Factor 5 stabilised. Available with white or black heads.



Part Number	Shank Length mm	Shank Diameter mm	Head Colour	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
POLY030WH	30	2.00	White	250	0.22	8.27
POLY040WH	40	2.00	White	250	0.29	9.46
POLY050WH	50	2.65	White	100	0.25	17.79
POLY065WH	65	3.35	White	100	0.48	26.77
POLY030BL	30	2.00	Black	250	0.22	8.74
POLY040BL	40	2.00	Black	250	0.29	9.63
POLY050BL	50	2.65	Black	100	0.25	18.97
POLY065BL	65	3.35	Black	100	0.48	27.66