



## THROUGHBOLTS

Suitable for use in non-cracked concrete over C20/25. • Min 5µm

Zinc Plated and  
Yellow Passivated

Part Number	Anchor Hole Size mm	Anchor Length mm	Thread Length mm	Max Fixture Thickness mm	Minimum Hole Depth mm	Quantity Per Box	Ship Wt.kg Per 100	Price £ Per 100
TB06045	6	45	18	5	35	100	1.26	54.40
TB06055	6	55	30	15	35	100	1.34	59.22
TB06085	6	85	60	45	35	100	2.12	63.00
TB08050	8	50	20	5	40	100	2.60	73.03
TB08065	8	65	30	20	40	100	3.14	78.12
TB08080	8	80	45	35	40	50	3.54	88.61
TB08100	8	100	60	55	40	50	4.08	93.20
TB08130	8	130	90	85	40	50	4.88	105.32
TB10065	10	65	30	8	50	50	4.80	98.32
TB10075	10	75	35	18	50	50	5.40	103.94
TB10090	10	90	55	33	50	50	6.32	113.97
TB10100	10	100	60	43	50	50	6.95	118.74
TB10120	10	120	80	63	50	20	8.20	134.29
TB10150	10	150	100	93	50	20	10.25	159.55
TB10175	10	175	100	118	50	20	12.30	171.83
TB12080	12	80	35	5	65	20	8.10	155.15
TB12100	12	100	55	25	65	20	9.60	163.08
TB12120	12	120	70	45	65	20	11.30	196.67
TB12140	12	140	90	65	65	20	13.00	216.29
TB12180	12	180	100	105	65	20	16.40	278.96
TB16105	16	105	55	10	85	20	19.85	303.83
TB16125	16	125	72	30	85	20	22.50	371.13
TB16150	16	150	90	55	85	20	26.18	414.01
TB16175	16	175	115	80	85	10	29.85	473.19
TB16220	16	220	125	125	85	10	35.00	559.20
TB20130	20	130	75	20	100	10	36.80	529.77
TB20160	20	160	100	50	100	10	45.20	589.42
TB20215	20	215	115	105	100	10	58.10	848.08
TB24180	24	180	105	45	120	10	69.00	1,256.24
TB24260	24	260	150	125	120	5	98.00	1,680.71

## THROUGHBOLTS

Suitable for use in cracked concrete and non-cracked concrete. • Min 5µm

Zinc Plated and  
Clear Passivated



Part Number	Anchor Hole Size mm	Anchor Length mm	Thread Length mm	Max Fixture Thickness mm	Minimum Hole Depth mm	Quantity Per Box	Ship Wt.kg Per 100	Price £ Per 100
ETA08075	8	75	20	10	60	100	2.99	103.12
ETA08095	8	95	40	30	60	100	3.60	110.09
ETA08115	8	115	60	50	60	100	4.24	123.47
ETA10090	10	90	20	10	75	50	5.88	142.79
ETA10110	10	110	40	30	75	50	6.88	173.06
ETA10130	10	130	60	50	75	50	9.90	190.86
ETA12110	12	110	30	15	90	25	9.92	211.99
ETA12125	12	125	45	30	90	25	11.0	257.51
ETA12160	12	160	80	65	90	25	13.60	338.16
ETA12180	12	180	80	85	90	25	15.00	364.67
ETA16135	16	135	35	15	110	20	21.60	452.49
ETA16170	16	170	70	50	110	20	26.30	554.57
ETA16200	16	200	80	80	110	10	32.00	641.93
ETA20165	20	165	50	30	125	10	44.1	1,287.50
ETA20195	20	195	70	60	125	10	50.5	1,545.00