

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Assembly foam
- **Application of the substance / the mixture** Construction chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
JCP Construction Products  
Unit 14 Teddington Business Park,  
Station Rd., Teddington, TW11 9BQ  
Tel: +44 208 943 1800  
Fax: +44 208 943 1140  
Web: www.jcpfixings.co.uk
- **Further information obtainable from:** jcpenquiries@owlett-jaton.com
- **1.4 Emergency telephone number:** +44 (0)208 943 1800 8.30am-5.00pm Monday to Friday

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1    H334      May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Carc. 2          H351      Suspected of causing cancer.  
STOT RE 2      H373      May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4    H332      Harmful if inhaled.  
Skin Irrit. 2    H315      Causes skin irritation.  
Eye Irrit. 2    H319      Causes serious eye irritation.  
Skin Sens. 1    H317      May cause an allergic skin reaction.  
STOT SE 3      H335      May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labelling:**  
diphenylmethanediisocyanate, isomers and homologues· **Hazard statements**

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

- P102 Keep out of reach of children.
- P260 Do not breathe gas.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: [www.feica.eu/PUinfo](http://www.feica.eu/PUinfo)

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

EUH204 Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Determination of endocrine-disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**SECTION 3: Composition/information on ingredients**· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 2)

**· Dangerous components:**

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	30-60%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-XXXX	tris(2-chloro-1-methylethyl)phosphate ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H302; Aquatic Chronic 3, H412	< 20%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<15%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<15%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-31-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 86675-46-9 Reg.nr.: 01-2119972940-30-xxxx	halogenated polyetherpolyol ⚠ Acute Tox. 4, H302	<15%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<10%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

**· After skin contact:**

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**· After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; call for medical help immediately.

**· 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****· 5.1 Extinguishing media****· Suitable extinguishing agents:**

Carbon dioxide.  
Fire-extinguishing powder.  
Foam.

(Contd. on page 4)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 3)

Water spray.

Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet.

- **5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information** Cool endangered receptacles with water spray.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Wear protective clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers / surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents, e.g. acetone, alcohol. Remove cured foam mechanically.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections** See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**

Ensure good ventilation / exhaust at the workplace.

Open and handle receptacle with care.

Do not pierce or burn even after use. Use only as directed on the label.

Do not mix with any other chemical products.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

This product is subject to regulations governing the storage of highly flammable aerosol products.

Storage rooms should be equipped with heat and smoke detectors.

Electrical equipment should be explosion-proof.

- **Information about storage in one common storage facility:**

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Store away from oxidising agents.

Store away from foodstuffs.

Store away from plastic, rubber, aluminum, light-metals.

- **Further information about storage conditions:**

Store in vertical position in closed original containers.

Store receptacle in a well ventilated area.

(Contd. on page 5)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 4)

- Protect from frost.
- Store at temperature from +5°C to +30°C.
- Store under lock and key and out of the reach of children.
- Keep container tightly sealed.
- Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

##### **CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

OEL (Ireland)	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> as -NCO; Sens.
---------------	---

##### **CAS: 115-10-6 dimethyl ether**

IOELV (EU)	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
OEL (Ireland)	Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm IOELV

##### **CAS: 75-28-5 isobutane**

OEL (Ireland)	Short-term value: 1000 ppm
---------------	----------------------------

##### **CAS: 74-98-6 propane**

OEL (Ireland)	Asphx
---------------	-------

#### · Regulatory information

OEL (Ireland): 2024 CoP for the Safety, Health and Welfare at Work  
IOELV (EU): (EU) 2019/1831

#### · DNELs

##### **CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	DNEL	20 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.05 mg/kg/Tag (General population, consumers)
Inhalative	DNEL	0.05 mg/m <sup>3</sup> (General population, consumers) 0.05 mg/m <sup>3</sup> (Workers)

#### · PNECs

##### **CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg

- **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

#### · Individual protection measures, such as personal protective equipment

#### · General protective and hygienic measures:

- Do not inhale gases / fumes / aerosols.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

EU

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 5)

**· Hand protection**

Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

**· Material of gloves**

Polyethylene gloves.

Recommended thickness of the material:  $\geq 0.020$  mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**Short-term contact  $\geq 10$  min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye/face protection**

Tightly sealed goggles

EN 166

**· Body protection:**

Protective work clothing.

**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Liquid

**· Colour:**

Different according to colouring

**· Odour:**

Characteristic

**· Odour threshold:**

Not determined

**· Melting point/freezing point:**

Not determined

**· Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol

**· Flammability**

Extremely flammable aerosol.

**· Lower and upper explosion limit****· Lower:**

+/- 1.5 Vol %

**· Upper:**

+/- 11.0 Vol %

**· Flash point:**

&lt;0 °C

(propellant)

**· Auto-ignition temperature:**

Not specified

**· Decomposition temperature:**

Not determined

**· pH**

-

Not applicable

**· Viscosity:****· Kinematic viscosity**

Not determined

(Contd. on page 7)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 6)

<ul style="list-style-type: none"> <li>· <b>Solubility</b></li> <li>· <b>water:</b> Insoluble Reacts with water</li> <li>· <b>Partition coefficient n-octanol/water (log value)</b> Not determined</li> <li>· <b>Vapour pressure:</b> &gt;500 kPa (in the container) &lt; 1*10<sup>-5</sup> mmHg w 25°C (MDI)</li> <li>· <b>Density and/or relative density</b></li> <li>· <b>Density at 20 °C:</b> ≤1.3 (PMDI) g/cm<sup>3</sup></li> <li>· <b>Relative density</b> Not determined</li> <li>· <b>Relative gas density</b> Not determined.</li> <li>· <b>Particle characteristics</b> Void</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>9.2 Other information</b> No further relevant information available</li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b> Rapidly curing foam dispensed by gaseous propellant from an aerosol container</li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b> &gt; +350 °C (propellant)</li> <li>· <b>Explosive properties:</b> Heating may cause an explosion.</li> </ul>	
<ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b> Void</li> <li>· <b>Flammable gases</b> Void</li> <li>· <b>Aerosols</b> Extremely flammable aerosol. Pressurised container: May burst if heated.</li> <li>· <b>Oxidising gases</b> Void</li> <li>· <b>Gases under pressure</b> Void</li> <li>· <b>Flammable liquids</b> Void</li> <li>· <b>Flammable solids</b> Void</li> <li>· <b>Self-reactive substances and mixtures</b> Void</li> <li>· <b>Pyrophoric liquids</b> Void</li> <li>· <b>Pyrophoric solids</b> Void</li> <li>· <b>Self-heating substances and mixtures</b> Void</li> <li>· <b>Substances and mixtures, which emit flammable gases in contact with water</b> Void</li> <li>· <b>Oxidising liquids</b> Void</li> <li>· <b>Oxidising solids</b> Void</li> <li>· <b>Organic peroxides</b> Void</li> <li>· <b>Corrosive to metals</b> Void</li> <li>· <b>Desensitised explosives</b> Void</li> </ul>	

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**  
Strongly reacts with water and other substances containing an active hydrogen atom.

(Contd. on page 8)



Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)

(Contd. of page 7)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

- **Acute toxicity**

Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)

**CAS: 86675-46-9 halogenated polyetherpolyol**

Oral	LD50	917 mg/kg (rat)
------	------	-----------------

**CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate**

Oral	LD50	632-2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4h	>7 mg/l /4-hr (rat)

- **Skin corrosion/irritation**

Causes skin irritation.

- **Serious eye damage/irritation**

Causes serious eye irritation.

- **Respiratory or skin sensitisation**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity**

Suspected of causing cancer.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause respiratory irritation.

- **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues**

EC50	1,640 mg/l (algae)
	>1,000 mg/l (daphnia) (OECD202)
	>100 mg/l (Sedimentation) (OECD209)
LC50	>1,000 mg/l (fish) (OECD)

- **12.2 Persistence and degradability** Not biodegradable.

- **12.3 Bioaccumulative potential** Does not accumulate in organisms.

- **12.4 Mobility in soil** No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

(Contd. on page 9)



**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

(Contd. of page 8)

- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**

Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Danger to drinking water if even small quantities leak into the ground.

**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Do not allow to enter surface or ground water.

Dispose of in a safe manner in accordance with local / national regulations.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

· **European waste catalogue**

15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP7	Carcinogenic
HP13	Sensitising

· **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**· **ADR**

1950 AEROSOLS

· **IMDG, IATA**

AEROSOLS

· **14.3 Transport hazard class(es)**· **ADR**· **Class**

2 5F Gases.

· **Label**

2.1

(Contd. on page 10)

Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)

(Contd. of page 9)

## · IMDG, IATA



- Class 2.1 Gases.
- Label 2.1

- 14.4 Packing group -

## · 14.5 Environmental hazards:

- Marine pollutant: No.

- 14.6 Special precautions for user Warning: Gases.

- Hazard identification number (Kemler code): -

- EMS Number: F-D,S-U

- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.

## · Transport/Additional information:

## · ADR

- Remarks: Exemption from ADR provisions by LQ principal (rule 3.4)
  - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg.
  - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.

- UN "Model Regulation": UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, REACH  
1272/2008/CE Regulation, CLP  
2020/878/UE Regulation

## · Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P3a FLAMMABLE AEROSOLS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 56, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 11)

Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)

(Contd. of page 10)

<ul style="list-style-type: none"> <li>· <b>Regulation (EC) No 273/2004 on drug precursors</b></li> </ul>
---

None of the ingredients is listed.
------------------------------------

<ul style="list-style-type: none"> <li>· <b>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</b></li> </ul>
---

None of the ingredients is listed.
------------------------------------

- **REGULATION (EU) 2024/590 on substances that deplete the ozone layer**

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H220 Extremely flammable gas.  
 H280 Contains gas under pressure; may explode if heated.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH204 Contains isocyanates. May produce an allergic reaction.

- **Recommended restriction of use**

The information stated above is based on current knowledge and applies to the product in the form in which it is used. Data concerning this product is presented in order to fulfill safety requirements and not to guarantee its specific properties.

In cases when application conditions are not subject to manufacturer's control, the responsibility for safe product use and obeying law regulations in particular, lies on the user's side.

Information in the appropriate technical data sheet of product.

- **Version number of previous version: 2**

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 ATE: Acute toxicity estimate values  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 Resp. Sens. 1: Respiratory sensitisation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Carc. 2: Carcinogenicity – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 12)

**Trade name: Expanding Foam Gun Grade B1 Fire Rated (JF750B1G)**

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 11)

· **\* Data compared to the previous version altered.**

Points marked with \* have changed from the previous version of the card