
## CONSTRUCTION PRODUCTS®

## Injection Resin Accessories



#### **INJECTION GUNS**



#### **Information**

- Fast and Effortless resin Injection
- JTOOL150 is ideal for DIY applications.
- JTOOL300 is designed for easy handling and it is built to last through repeated use in all job site conditions.
- Compatible with other cartridges commercially available

# **COMPATIBLE RESINS**

**COMPATIBLE RESINS** 



- Fast and Effortless resin Injection
- Robust design for all jobsite conditions
- Built to Last Through Repeated Use
- JTOOL 410 has a lightweight design which make it ideal for professional
- Compatible with other cartridges commercially available















- · Fast and Effortless resin Injection
- · Robust design for all jobsite conditions
- · Easy to use
- Built to Last Through Repeated
- · Compatible with other cartridges commercially available

#### **COMPATIBLE RESINS**







- Fast and Effortless resin Injection
- · Robust design for all jobsite conditions
- Fast and Effortless resin Injection
- Built to Last Through Repeated
- · Compatible with other cartridges commercially available

#### **COMPATIBLE RESINS**









O Unit 14 Teddington Business Park Station Rd., Teddington, Middlesex TW11 9BQ



Tel: +44 (0)20 8943 1800 Fax:+44 (0)20 8943 1140




jcpenquiries@owlett-jaton.com www.jcpfixings.co.uk





#### Injection Resin Accessories





- Metal round wire brushes with a wooden handle
- Ideal for cleaning of the dust from the drilled holes prior to installation of anchors
- To be used together with blow out pump for cleaning of the holes
- Ensure correct installation and to achieve the required resistance.
- High durability for frequent use

RANGE DATA									
Part Number	Brush Diameter d <sub>b</sub>	Brush length L <sub>b</sub>	Total length L	Drill hole Diameter d <sub>o</sub>	Threded Rod Diameter				
	mm	mm	mm	mm	mm				
CB08	8	128	220	6 to 8	M6				
CB10	10	128	220	8 to 10	M8				
CB12	12	128	220	8 to12	M8 to M10				
CB16	16	128	220	12 to 16	M10 to M14				
CB20	20	128	220	14 to 20	M14 to M16				
CB25	25	128	250	20 to 24	M16 to M20				
CBW30	30	128	300	26 to 30	M24				



 Manual pump made of plastic for cleaning drilled holes with the diamter over 10mm and maximum depth of 250 mm to be used prior to installation of anchors

#### **Injection Tool Accessories**



Mixer Nozzle JMN130

Mixer nozzle suitable to be used with

- J-Fix Polyester Resins with or without styrene
- J-Fix Epoxy Acrylate Resin
- J- Fix Vinylester Resin and its winter grade version.
- Other similar products

Extension Tube JMN190

250 mm extension tube to be used with JMN130 or similar nozzles for deep drill holes.

#### Mixer Nozzle JMN150E

Mixer nozzle suitable to be used with

- J-Fix Pure Epoxy Resin
  J-Fix Ultra bond Resin
- Other similar epoxy products
- Unit 14 Teddington Business Park Station Rd., Teddington, Middlesex TW11 9BQ



Tel: +44 (0)20 8943 1800 Fax:+44 (0)20 8943 1140



jcpenquiries@owlett-jaton.com www.jcpfixings.co.uk





### Injection Resin Accessories





#### **Accessories for Fixing Into Masonry**



- Perforated Sleeves made of polypropylene (gray coluor)
- Ideal for Resins such as Polyester and Vinylester and Epoxy Acrylate when used in hollow base materials such as brick and blocks or hollow concrete planks
- With collar to ensure vertical alignment of studs during installation
- Allowing Resin to evenly permeate
- Resistance depends on the resin to be used and base material characteristics.

RANGE DATA									
Part number	Sleeve length (d¸X L¸)	Hole Diameter (d <sub>o</sub> )	Hole depth (h <sub>0</sub> )	Effective embed- ment(h <sub>ef</sub> )	Stud Size				
	mm	mm	mm	mm	mm				
JNSLM08/12	15 x 85	16	90	85	M8 to M12				
JNSLM08/12L	15 x 130	16	135	130	M8 to M12				
JNSLM16	20 x 85	22	90	85	M16				







- Perforated Sleeves made of carbon Steel
- Can be cut on site to the required length to have deep embedment depth where
- Ideal for Resins such as Polyester and Vinylester and Epoxy Acrylat when used in hollow base materials such as brick and blocks or hollow concrete planks
- Allowing Resin to evenly permeate
- Resistance depends on the resin to be used and base material characteristics.

RANGE DATA								
Part number	Sleeve length (d¸X L¸)	Hole Diameter (d <sub>o</sub> )	Stud Size					
	mm	mm	mm					
JMMSM08	8.7 X 1000	12	M8					
JMMSM10/12	12.5 X 1000	16	M10 - M12					
JMMSM16	18 X 1000	22	M16					
JMMSM20	22 X 1000	26	M20					









jcpenquiries@owlett-jaton.com www.jcpfixings.co.uk

